

BHM1SL & BHM2SL Downflow Fan Heaters - Double Insulated

These are ideal for bathrooms, kitchens and areas requiring localised, controllable heat. The BHMSL Heatflow is double insulated for ease of installation. It features heating control options with SL wireless controllers, comfort and setback temperature settings and automatic overheat safety cut-out.

- 1kW or 2kW rating
- Wireless controlled by separately purchased SL controller
- One SL controller can operate multiple SL heaters
- Choice of SL controllers:
 - SLPB: Run-back timer and thermostat
 - SLVT: Run-back timer and adjustable thermostat
 - SLTI: 7-day timer and adjustable thermostat
- Double insulated class II appliance
- 2 automatic safety cut-outs for additional safety
- Fitted power supply cable
- Secure wall fixing
- Finished in white



Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Height	Depth	Width	Weight	Finish
BHM1SL	1	190	115	305	2.0	White
BHM2SL	2	190	115	305	2.0	White

Basic features of SL controllers:

SLPB & SLVT Features

- 3 operating modes: Basic, Timer & Temperature Control
- Choice of 3 time periods in Timer mode: 5, 15 or 30 minutes
- Comfort and setback temperature settings
- Easy-to-read digital display and temperature control buttons with SLVT

SLTI Features

- 7-day timer with electronic thermostat
- 3 heating periods per day
- 4 operating modes: Programme, Boost, Setback & Comfort
- Comfort and setback temperature settings
- Electronic lock