

LST500RX & LST800RX Panel Heaters - Wireless Controlled

Ideal for schools, nurseries, retirement homes, hospitals and anywhere where safety is paramount.

The LST wireless controlled panel heaters are designed with a maximum surface temperature of 43°C, complying with NHS Estates Health Guidance Notes, to minimise the risk of burn injuries. They are easy to install, very quiet in operation and perfect for environments with vulnerable people such as children and elderly residents.

- 0.5kW or 0.8kW rating
- Maximum surface temperature of 43°C to comply with NHS Estates Health Guidance Notes
- Very quiet operation
- Wireless controlled by separately purchased CRX2 controller
- One CRX2 controller can operate multiple RX heaters
- CRX2 controller is compatible with separately purchased MRX1 Multizone controller for 'zoning' of the heating system
- Splash proof to IP24 for use in bathrooms and other wet areas
- Hinged wall mounting system for easy installation and cleaning
- Automatic safety cut-out
- Fitted with 1.8m of supply cable
- Finished in white



Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Height	Depth	Width	Weight
LST500RX	0.5	430	93	832	6.3
LST800RX	0.8	430	93	1195	8.7

CRX2 Energy Saving Features

- 6 temperature programmes per day
- 7-day heating programmes per week
- Maintains temperature within 0.5°C
- Set temperature in 0.5 degrees increments
- Reduced power consumption in standby mode

